

## IMPACT HAMMER SPECIFICATIONS

		Model:	<b>70</b>	<b>115</b>	<b>160</b>	<b>220</b>	<b>275</b>	<b>345</b>
Ram Weight	lbs		7000	11500	16000	22000	27500	34500
Maximum Stroke	feet		3	4	4	4	4	4
Minimum Stroke	feet		1	1	1	1	1	1
Hammer Weight (bare)	lbs		13400	17000	28600	35000	47650	54650
Hyd Hose Length	feet		100	100	150	150	150	150
Hyd Hose Weight (full)	lbs		850	850	1340	1340	1340	1500
50 Ft. Hose Ext. (full)	lbs							
Depth	D inches		38	36	46	48	54	60
Width	W inches		20	26	32	32	36	36
Height (bare)	H ft-in		15'-5"	19'-9"	20'-3"	20'-3"	22'-8"	22'-8"

## POWER UNIT SPECIFICATIONS

		Model:	<b>H108</b>	<b>200</b>	<b>220</b>	<b>335</b>	<b>335</b>	<b>535</b>
Engine:			Diesel	Diesel	Diesel	Diesel	Diesel	Diesel
Horsepower			108	200	220	335	335	535
Hydraulic fluid capacity	gal		60	275	275	275	275	385
Drive pressure	psi		2500	2500	4500	4500	5500	4800
Drive flow	gpm		48	100	70	90	90	160
Stroke System Press	psi		1000	1500	1500	1500	1500	1500
Stroke System Flow	gpm		10	10	10	10	10	7
Fuel Capacity	gal		75	130	130	130	130	150
Weight (no fuel)	lbs		3400	9400	9400	9600	9600	14300
Length	ll inches		96	126	126	126	126	154
Width	ww inches		45	60	60	60	60	60
Height	hh inches		52	76	76	79	79	95

